

Product Name: MASONRYSAVER V.O.C. COMPLIANT SOLVENT-BASE WATER REPELLENT®**MSDS Number: VC-29 CAS Number: Mixture Date: 03-04-2010 Prepared by: Greg Herbert****SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION**

PRINCIPAL HAZARDOUS COMPONENT(S) (CHEMICAL & COMMON NAMES)	P.C.	THRESHOLD LIMIT VALUE (UNITS)
PCBtF	50ppm	100ppm
Aliphatic Hydrocarbon	100ppm	100ppm
Modified Oligomeric Polysiloxane	N.E.	N.E.

Percentage content of ingredients withheld as a trade secret pursuant to Massachusetts regulations

SECTION 2 - PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance and odor: -----Clear liquid with a solvent odor
Boiling point: -----282° F
Vapor pressure (mm Hg and temperature): -----2mm Hg.
Vapor density (air = 1): -----6.0
Evaporation rate: -----(ether = 1) .9
Solubility in water: -----N.E.
Water reactive: -----N.E.
Specific gravity: -----.959
% volatile by volume: -----

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Flash point and method used: -----115° F Closed Cup
(WARNING! FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE.)
Auto-ignition temperature: -----No Data
Flammability limits in air % by volume: -----N.E.
Extinguishing media: -----REGULAR FOAM or CARBON DIOXIDE
 or DRY CHEMICAL
Special fire fighting procedures: -----Product is flammable. Wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode when fighting fires.
Unusual fire and explosion hazards: -----Product is flammable. Vapors are heavier than air - may travel along the ground or be moved by ventilation & ignited by heat, pilot lights, other flames & ignition sources at locations distant from material handling point.

SECTION 4 - REACTIVITY HAZARD DATA

Stability: -----Stable
Conditions to avoid: -----Product is flammable. No heat, pilot lights, open flame, or sparks.
Incompatibility (materials to avoid): -----Avoid contact with strong oxidizing agents.
Hazardous decomposition products: -----At Hydrolysis: Methyl Alcohol
Hazardous polymerization: -----Will not occur.
Conditions to avoid: -----Storing in temperatures above 100 °F.

