

# MASONRYSAVER MASONRY CLEANER/DEGREASER

## PRODUCT DATA

### MASONRYSAVER® CLEANER/DEGREASER

**MANUFACTURER:** SaverSystems  
Richmond, IN 47374  
800-860-6327 Fax 765-935-4999  
www.saversystems.com

## DESCRIPTION

**MasonrySaver Masonry Cleaner/Degreaser®** is a super concentrated alkaline-based cleaner formulated to clean a variety of masonry surfaces including concrete, brick and stone. MasonrySaver Masonry Cleaner/Degreaser® penetrates deep into the substrate to remove petroleum-based contaminants such as oils, dirt, grime and even efflorescence. MasonrySaver Masonry Cleaner/Degreaser® is an environmentally safe, biodegradable alternative to other harsher products, such as phosphoric acid or acid-based cleaners.

## USES

MasonrySaver Masonry Cleaner/Degreaser® cleans these surfaces:

- Loading Docks
- Garage Floors
- Driveways
- Parking Garages
- Industrial Floors
- Machine Shops
- Auto Repair Facilities

**LIMITATIONS:** DO NOT USE ON COMPOSITION FLOORS, WATER-BASE PAINTED SURFACES, OR ALUMINUM.

## BENEFITS

- Non-toxic
- Deep penetration
- Will not harm drains, plants, or environment
- Pleasant odor
- Does not leave residue

## DIRECTIONS FOR USE

**Dilution:** Mixing: Use 10 parts water to 1 part MasonrySaver Masonry Cleaner/Degreaser® to clean:

- |                |                 |
|----------------|-----------------|
| • Counter Tops | • Painted Walls |
| • Bathrooms    | • Woodwork      |
| • Linoleum     | • Automobiles   |
| • Tile Floors  | • Storm Doors   |
| • Boats        | • Garbage Cans  |

**FULL STRENGTH:** Use MasonrySaver Masonry Cleaner/Degreaser® to clean:

- |                 |              |
|-----------------|--------------|
| • Floor Wax     | • Heel Marks |
| • Smoke Film    | • Grease     |
| • Finger Prints | • Ovens      |

## APPLICATION

For general cleaning of dirt, grime, spots and stains, simply spray MasonrySaver Masonry Cleaner/Degreaser® on the area to be cleaned, wait a minute or two and wipe off.

For oil staining on concrete floors and driveways, do not dilute the product or pre-wet the surface. Apply MasonrySaver Masonry Cleaner/Degreaser® full strength by pouring or spraying to the areas to be cleaned. Work the cleaner into the stained area using a stiff broom or nylon brush. Allow the product to work for approximately 20-30 minutes before rinsing. Rinse with clean water. Rinsing with high pressure water and with heated water will expedite cleaning. For severe stains, multiple coats of cleaner may be needed.

## CAUTIONS

**Keep out of reach of children.** Contains alkaline detergents. If swallowed give vinegar or fruit juice, followed with olive oil.

**External:** Flood with water, wash with vinegar.

**Eyes:** Wash with 5% boric acid solution. Flood eyes with water. If irritation persists, see physician.

## LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited, in all events, to supplying sufficient product to re-treat the specific areas to which defective product has been applied. This warranty does not cover the cost of labor for application. SaverSystems shall have no other liability including direct, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages so this limitation or exclusion may not apply to you. This warranty gives you specific legal rights. You may also have other rights, which vary from state to state.

## PACKAGING

Available in thirty-two ounce spray bottles and one gallon recyclable plastic containers.

## TRANSPORT AND STORAGE

MasonrySaver Masonry Cleaner/Degreaser® is not considered hazardous under Department of Transportation (DOT) regulations. Do not stack pallets. Keep from freezing.

## PHYSICAL PROPERTIES

**COMPOSITION**..... Strongly alkaline

**SPECIFIC GRAVITY @ 25°C**..... (1.06)

**DENSITY**..... 8.80 lb/gal

**FLASH POINT**..... None

**V.O.C. CONTENT**..... Less than 50 g/l

**SHELF LIFE**..... 1 year in original unopened container

**FREEZE THAW STABILITY**..... Protect from freezing.