

#### MANUFACTURER:

**SaverSystems**  
Richmond, IN 47374  
800-860-6327  
Fax: 765-935-4999  
www.masonrysaver.com

#### DESCRIPTION

MasonrySaver No-Rinse Concrete Etch is a hydrofluoric acid-etching material designed for etching concrete surfaces prior to coating or sealing. A thin film of Etch will etch any silica-containing surface in as little as 15 seconds. Because of its unique chemistry, a surface treated with MasonrySaver No-Rinse Concrete Etch does not need to be rinsed prior to sealing. After using MasonrySaver No-Rinse Concrete Etch, a protective sealer such as MasonrySaver Decorative Concrete Sealer, may be applied directly over the stained and etched surface once the substrate has completely dried.

#### USES

Use MasonrySaver No-Rinse Concrete Etch to etch concrete, brick or masonry surfaces prior to staining or sealing. The etching properties of the product allow the user to seal the surface, once it has been properly stained, without the need for further preparation or rinsing.

#### AVANTAGES

- Etches all surfaces such as concrete, stone, tile or brick
- Only generates the etching compound upon evaporation and contact with SiO<sub>2</sub> or metal oxide
- Doesn't require neutralization or rinsing
- Saves time! Topcoats may be applied within hours of application versus days with HCL
- Improved coating adhesion

#### DIRECTIONS FOR USE

**Surface Preparation:** Always test in an inconspicuous area to ensure desired results. Protect foliage and all applicable surrounding areas including wood, glass, aluminum, asphalt, roofing, vinyl siding and painted surfaces. Beware of wind drift. **Do not dilute.**

#### APPLICATION

MasonrySaver No-Rinse Concrete Etch should only be used on bare, unsealed surfaces. Brush surface to be treated with a stiff brush to remove loose particles. Mix container contents thoroughly to ensure uniformity. Apply with a paint pad, tight nap roller cover or pump type sprayer. (Splash gloves and eye protection such as splash goggles should be used along with a NIOSH approved respirator equipped with a multi gas/vapor filter protecting against ammonia and other organic vapors.)

**Drying time:** 15 – 30 minutes, depending upon conditions.

**Coverage:** 200-400 square feet per gallon on concrete. Coverage rates will vary based on the porosity of the substrate.

#### CLEAN UP

Thoroughly rinse spray equipment with clean water. Clean brushes and rollers with soap and water. Rinse thoroughly.

#### CAUTIONS

Danger- Poison. Keep out of reach of children. Keep container closed. Avoid contact with skin, eyes, and clothing. Avoid breathing vapors or mist. . The use of chemical splash gloves, splash goggles and a NIOSH approved respirator, effective against ammonia inhalation, should be used when applying this product.

#### FIRST AID

**If inhaled:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. Immediately get medical attention.

**If swallowed:** Obtain emergency medical attention. If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/ physician.

**For skin contact:** Rinse thoroughly with plenty of water for at least 20 minutes and take medical advice. Remove all contaminated clothing and footwear. Obtain medical attention.

**For eye contact:** In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

For additional information for this product, consult the Safety Data Sheet available at [www.masonrysaver.com](http://www.masonrysaver.com).

#### LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

#### PACKAGING

Available in one-gallon plastic containers.

#### TRANSPORT AND HANDLING

MasonrySaver No-Rinse Concrete Etch is not considered hazardous under Department of Transportation (DOT) regulations. Do not stack pallets. Keep from freezing.

#### PHYSICAL PROPERTIES

COLOR . . . . . Clear  
ODOR . . . . . Slight acidic odor  
SHELF LIFE . . . . . 24 months when unopened