

MANUFACTURER:

SaverSystems
Richmond, IN 47374
800-860-6327
Fax: 765-935-4999
www.masonrysaver.com

DESCRIPTION

MasonrySaver Decorative Concrete Sealer is a non-yellowing acrylic polymer blend sealer formulated for use on properly cured stamped concrete surfaces. Designed for use on both interior and exterior concrete, MasonrySaver Decorative Concrete Sealer is suitable for use on a variety of surfaces where a durable gloss finish is desired including concrete patios, driveways, sidewalks and even garage floors.

USES

MasonrySaver Decorative Concrete Sealer dust proofs concrete with a durable acrylic blend resin. On surfaces that have been previously stained using MasonrySaver No-Rinse Acid Etching Stain, MasonrySaver Decorative Concrete Sealer leaves an attractive, non-yellowing durable gloss finish that protects concrete from damage and color loss due to ultra-violet light, moisture and abrasion/wear.

ADVANTAGES

- Water-based formula for easy application and rapid dry time
- Provides an attractive, gloss finish to stained concrete
- Protects stained concrete surfaces from color fade
- Seals concrete surfaces making them washable and easy to maintain
- Non-yellowing, clear finish
- Durable concrete protection with "hot tire" resistance
- Can be applied over previously treated surfaces with solvent-base sealer

DIRECTIONS FOR USE

Weather Conditions: Do not proceed with application if any of the following occur: temperature falls below 50°F or rainfall is predicted within eight hours of application, or when surface is frozen. Application should only be made when surface temperature is between 50-90°F and is thoroughly dry.

Limitations: Not suitable for use over asphalt surfaces. This product is designed for use on horizontal or vertical surfaces. Do not use on below-grade surfaces that are subject to severe hydro-static pressures. When using in areas subjected to hot tire traffic, allow adequate time for product to cure before putting the area back into surface. When applying over previous coating, hot tire resistance maybe compromised. Do not use if the area will be exposed to softer, high performance tires.

Surface Preparation: Always test in an inconspicuous area to ensure desired results. When using, surface to receive application should be clean and dry. Absorbed moisture should not be present. New construction should cure for a period of no less than 28 days and should be clean and dry. If necessary, the surface should be thoroughly cleaned per label instructions, using MasonrySaver Safer Acid Cleaner, to remove dust, oil, wax,

curing compounds, efflorescence, coatings and other foreign materials in order to expose a clean, sound surface. Protect all adjacent glossy surfaces, paint films, windows, plant life, asphalt based material and all other non-targeted surfaces from overspray and run-down. Cover all openings including windows and doors prior to application. During use, avoid wind drift that may injure pedestrians, damage vehicles or adjacent properties.

After cleaning with an acid cleaner, or following the application of an acid-based concrete stain, it is extremely important to rinse the surface thoroughly to bring the substrate to a neutral ph level (7). Testing with ph paper should be done prior to sealing to insure that a neutral ph has been achieved. Applying sealer over an acidic substrate will most likely result in failure. After rinsing, surface should be allowed to dry a minimum of three to five days prior to sealing. When coating new concrete, the concrete should first be etched per label instructions, using MasonrySaver No-Rinse Concrete Etch, before applying MasonrySaver Decorative Concrete Sealer. Chemicals or other cleaning compounds used to facilitate the removal of these foreign materials must be removed thoroughly before applying the product.

Mixing: Material may separate during long-term storage so mix thoroughly before use.

Equipment: MasonrySaver Decorative Concrete Sealer may be sprayed applied using a pump-up, garden type sprayer with fan type nozzle, with an airless industrial sprayer or by roller. If roller applied, use a short nap cover.

APPLICATION

Apply two uniform coats of material to new, previously untreated concrete surfaces. Allow the first coat of material to dry sufficiently to walk on, but not more than 4 hours, prior to application of the second coat. Avoid puddling or ponding of product: brush or roll material until it thoroughly penetrates the surface. Block all drains and use absorptive coverings to contain run-off or excess material. Use soap and water to remove overspray as soon as possible.

Drying time: One to two hours, depending on temperature and humidity. Allow four to six hours cure time before exposing to foot traffic. Allow four days cure time before exposure to heavy traffic, such as forklifts, automobiles, etc. If applying a finish wax, allow 48 hours cure time before waxing

Coverage: 100 - 150 square feet per gallon on concrete. Coverage rates will vary based on the porosity of the substrate.

WAXING: For best long-term results on interior surfaces, when cured, MasonrySaver Decorative Concrete Sealer should be sealed and protected with a stamped concrete waxing compound, such as MasonrySaver #25 Floor Finish. Failure to apply and maintain a wax coating will result in premature failure of the product. On exterior surfaces no wax coating is necessary.

CLEAN UP

Remove any overspray immediately with soap and water. Dry film can be removed using a razor scraper. Thoroughly rinse spray equipment with clean water. Clean applicators with soap and water. Rinse thoroughly.

CAUTIONS

Keep out of reach of children. Keep container closed. Eye irritant. Avoid contact with eyes, mucous membranes and prolonged contact with skin. The use of chemical splash gloves and a NIOSH approved respirator, effective against ammonia inhalation, is highly recommended when using this product.

FIRST AID

If inhaled: In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air.

If swallowed: Rinse mouth. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Immediately call a POISON CENTER or doctor/physician.

For skin contact: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

For additional information for this product, consult the Safety Data Sheet available at www.masonrysaver.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in one- and five-gallon recyclable plastic containers.

TRANSPORT AND HANDLING

MasonrySaver Decorative Concrete Sealer is not considered hazardous under Department of Transportation (DOT) regulations. Do not stack pallets. **Keep from freezing.**

MAINTENANCE

Remove all contaminants which might stain or abrade treated surfaces as quickly as possible to minimize staining and abrasion. Occasional cleaning with a mild detergent and water will generally restore treated surfaces to original appearance. When MasonrySaver Decorative Concrete Sealer begins to appear worn from the surface, a single coat of material may be applied once surface has been properly prepared. For surfaces that have been waxed, follow the waxing product's label directions for maintaining the waxed surface. Avoid applying maintenance coat more frequently than every 18 - 24 months to avoid excessive build-up of material on surface. When build-up of product does become excessive, surface should be thoroughly stripped of product followed by application of two coats of material.

PHYSICAL PROPERTIES

COMPOSITION	Proprietary Waterborne Emulsion
DENSITY	8.5 lb/gallon
FLASH POINT	None
VOC CONTENT	26 g/L
SHELF LIFE	36 months
FREEZE THAW STABILITY	No