

MANUFACTURER:

SaverSystems
Richmond, IN 47374
800-860-6327
Fax: 765-935-4999
www.masonrysaver.com

DESCRIPTION

MasonrySaver #25 Floor Finish is a highly durable water-based acrylic polymer interior floor finish. Formulated to be applied directly over MasonrySaver Decorative Concrete Sealer, #25 Floor Finish provides a rich, gloss finish, designed for high speed buffing, that resists dirt and floor scuffing and prolongs the floor life of Decorative Concrete Sealer.

USES

MasonrySaver #25 Floor Finish has been formulated for use on interior horizontal concrete surfaces. Surface and air temperature should be between 50°F and 90°F. Do not apply to surfaces that are damp or wet.

ADVANTAGES

- Provides a rich, gloss finish
- Designed for high speed buffing
- Prolongs the floor life of Decorative Concrete Sealer
- Resists dirt and floor scuffing

DIRECTIONS FOR USE

Surface Preparation: MasonrySaver #25 Floor Finish has been formulated for use on interior horizontal concrete surfaces. Surface and air temperature should be between 50°F and 90°F. Do not apply to surfaces that are damp or wet.

Surface Preparation (New Floors): New floors should first be properly cleaned, stained and sealed per manufacturer's directions. When sealing, use MasonrySaver Decorative Concrete Sealer, or a comparable product. Allow sufficient time for sealer to properly cure prior to applying #25 Floor Finish.

Surface Preparation (Previously Sealed Floors): Where wax build-up is evident, strip floors thoroughly to remove old wax and floor finish. Rinse floor thoroughly with clear water and allow to dry. If sealer coat has broken down to an uneven finish, reseal the floor using MasonrySaver Decorative Concrete Floor Finish prior to applying #25 Floor Finish.

APPLICATION

Work with clean equipment. MasonrySaver #25 Floor Finish is best applied using a mop or pad applicator. Before use, soak mops in water and ring out tightly so they absorb less finish and are easier to clean. Apply finish in uniform light to medium coats. Allow each coat to dry before applying additional coats. Coat traffic lanes more than other areas and work additional coats toward the edges. Recommended application is to apply three coats of finish in traffic areas for every single coat of finish in non-traffic areas. A minimum of two coats of finish should be applied to all non-traffic areas.

Cleaning and Maintenance: Remove all contaminants which might stain or abrade treated surfaces as quickly as possible to minimize staining and abrasion. Daily sweeping and dust mopping is critical for any floor care program. Damp mop with a neutral cleaner to remove dirt and other surface contaminants prior to buffing. MasonrySaver #25 Floor Finish can be high-speed buffed to achieve a rich, high gloss finish. A maintenance coat of #25 Floor Finish should be applied when the floor begins to exhibit an uneven sheen. For reapplications, three coats of finish should be applied to traffic areas and a single coat of finish should be applied in non-traffic areas.

Coverage Rate: 1,500 - 2,000 sq. ft. per gallon per coat. Minimum of two coats in non-traffic areas and six coats in traffic areas recommended.

Drying time: Allow at least 24 hours to cure prior to buffing.

Coverage: 1,500 - 2,000 sq. ft. per gallon per coat. Minimum of two coats in non-traffic areas and six coats in traffic areas recommended.

CLEAN UP

Thoroughly rinse all equipment with clean water. Clean mops and pads with soap and water. Rinse thoroughly.

CAUTIONS

Keep out of reach of children. Use normal safety precautions and wear appropriate protective gear when handling product. Dispose of container in proper method as required by local codes. May cause skin or eye irritation. Do not ingest.

FIRST AID

If inhaled: Remove to fresh air.

If swallowed: Induce vomiting, but ONLY if victim is fully conscious. Call a physician.

For skin contact: Wash off immediately with plenty of water. If skin irritation persists, call a physician.

For eye contact: Rinse thoroughly with plenty of water, removing contact lenses if present and easy to do so. If irritation persists, get medical advice/attention.

For additional information for this product, consult the Safety Data Sheet available at www.masonrysaver.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects. SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in one-gallon plastic containers.

TRANSPORT AND HANDLING

MasonrySaver #25 Floor Finish is not considered hazardous under Department of Transportation (DOT) regulations. Do not stack pallets. **Keep from freezing.**

MAINTENANCE

Remove all contaminants which might stain or abrade treated surfaces as quickly as possible to minimize staining and abrasion. Occasional cleaning with a mild detergent and water will generally restore treated surfaces to original appearance.

PHYSICAL PROPERTIES

COLOR Milky White
ODOR Light Ammonia
WEIGHT 8.5 lb/gallon
FLASH POINT None
VOC CONTENT >100 g/l
SHELF LIFE 36 months