

MANUFACTURER:

SaverSystems
Richmond, IN 47374
800-860-6327
Fax: 765-935-4999
www.chimneyrx.com

DESCRIPTION

Chimney RX Elastomeric Flashing Sealant is a black, elastomeric sealant specially formulated for permanent adhesion to asphalt shingles, aluminum flashing, brick, and other chimney and roofing materials.

USES

Elastomeric Flashing Sealant is excellent for use in stopping problem leaks around the base of chimneys, stacks, and vents. It is also great for sealing around skylights. Elastomeric Flashing Sealant repairs flashings that have been tarred, retarred, or cracked.

ADVANTAGES

- Stops leaks around chimneys, stacks, and vents
- Stays flexible over time
- Easy brush-on application
- Soap and water cleanup

DIRECTIONS FOR USE

Weather Conditions: Do not use in cold, damp, rainy weather or product may wash away. Allow at least 12 hours of dry, clear weather for proper curing. Apply at temperatures of 45°F and rising.

Limitations: This product is not intended for interior use, exterior below grade use, or for resistance to hydrostatic pressure.

Surface Preparation: Clean surfaces to which product will be applied with stiff brush to remove any dust, dirt, or debris.

APPLICATION

Stir product well. Apply approximately 1/8" of coating to the surface to be sealed. Make sure product fills all cracks and holes. Apply Elastomeric Flashing Sealant so that it extends beyond the problem area about one inch.

Note: On hot days Elastomeric Flashing Sealant will dry quickly. Work in 2-3 ft. sections. Use of duct tape will produce clean edges and enhance the appearance of the repair.

Drying time: Dries to touch in 30 - 60 minutes. Product cures completely within 6 - 12 hours depending on temperature and humidity.

Coverage: One half gallon container will cover approximately 14 square feet.

CLEAN UP

Use soap and water while product is still wet. Remove Elastomeric Flashing Sealant from tools immediately after each use by scrubbing with a stiff brush. To clean inadvertent spills from roofs, etc., remove excess and clean remaining Elastomeric Flashing Sealant with a stiff nylon scrub brush and water. Rinse thoroughly.

CAUTIONS

Keep out of reach of children. Respiratory protection is not generally required during normal use and handling. The use of protective gloves and chemical splash goggles is recommended. Wash thoroughly after handling. Close container after each use. California Proposition 65: This product contains crystalline silica, a chemical known to the State of California to cause cancer.

FIRST AID

If inhaled: In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air. Ensure fresh air breathing. Allow the victim to rest.

If swallowed: Rinse mouth. Obtain emergency medical attention. Do NOT induce vomiting unless directed to do so by a physician.

For skin contact: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention. Wash contaminated clothing before reuse.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Seek medical attention immediately.

For additional information for this product, consult the Safety Data Sheet available at www.chimneyrx.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in half-gallon recyclable plastic containers.

TRANSPORT AND HANDLING

Elastomeric Flashing Sealant is not considered a hazardous material or substance under U.S. Department of Transportation (DOT) regulations. Store product in a cool, dry place inaccessible to children and animals. **Keep from freezing.**

PHYSICAL PROPERTIES

COLOR Black
SOLVENT Water
DENSITY 11.6 lb/gal
SHELF LIFE 24 months when unopened