

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Trade name : Defy Interior Clear Wood Finish

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Sealing Interior Wood Surfaces

**1.3. Details of the supplier of the safety data sheet**

SaverSystems, Inc.  
800 S. 7th Street  
Richmond, 47374 - U.S.A.  
T (765) 966-5084

**1.4. Emergency telephone number**

Chemtel : 1 (800) 255-3924 24/7

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GHS-US classification**

No additional information

**2.2. Label elements****GHS-US labelling**

Signal word (GHS-US) : Not classified  
Hazard statements (GHS-US) : Not classified  
Precautionary statements (GHS-US) : P280 - Wear protective gloves, eye protection  
P405 - Store away from children  
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS-US)**

No data available

**SECTION 3: Composition/information on ingredients****3.1. Substance**

Not applicable

Full text of H-phrases: see section 16

**3.2. Mixture**

Name	Product identifier	%	GHS-US classification
2-Butoxyethanol	(CAS No) 111-76-2	5 - 9	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Dimethylol-5,5-dimethylhydantoin	(CAS No) 6440-58-0	~ 0.08	Acute Tox. 4 (Oral), H302

**SECTION 4: First aid measures****4.1. Description of first aid measures**

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : In all cases of doubt, or when symptoms persist, seek medical advice. Move the affected person away from the contaminated area and into the fresh air.

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash off immediately with soap and plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Suspected of damaging fertility or the unborn child.
Symptoms/injuries after inhalation	: Overexposure may cause : Headaches. The inhalation of airborne droplets or aerosols causes irritation of the respiratory tract.
Symptoms/injuries after eye contact	: In fine dispersion/spraying/misting: May cause eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Use media as appropriate for surrounding material . Foam. Dry powder. Carbon dioxide. Water spray. Sand.
------------------------------	---

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection. In case of fire: Wear self-contained breathing apparatus.
Other information	: Oxygen evolution decomposition may burst sealed containers and accelerate the burning rates of other combustible materials. Damp material in contact with paper, wood, cloth, etc. may cause spontaneous combustion of the organic material.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid inhalation of vapour and spray mist. Avoid skin and eye contact. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Use personal protective equipment as required. Use suitable eye protection and gloves. For further information refer to section 8 : Exposure-controls/personal protection.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Small spills may be flushed with large amounts of water; larger spills should be collected for disposal. Prevent large quantities from entering sewers, watercourses or low areas. Dispose of contents/container to comply with applicable local, national and international regulations.
-------------------------	---

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Surface will become slippery when wet or damp.
-----------------------------------	--

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- Precautions for safe handling : Keep out of reach of children. Do not breathe Wet misty spray . Avoid contact during pregnancy/while nursing. Wear goggles if splashing or spraying is anticipated. Wear suitable gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Wash contaminated clothing prior to re-use. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Use good personal hygiene practices. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep locked up and out of reach of children. Keep only in the original container in a cool well ventilated place. Store away from freezing (avoid freezing during storage). Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep container closed when not in use.
- Incompatible materials : Strong acids, bases. Oxidizing agents.
- Heat and ignition sources : Remove all sources of ignition.
- Special rules on packaging : Correctly labelled.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

### 8.2. Exposure controls

- Appropriate engineering controls : Ensure adequate ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Personal protective equipment : Gloves. Protective clothing. Protective goggles. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves. rubber gloves.
- Eye protection : Wear chemical splash goggle.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask.
- Environmental exposure controls : Avoid discharge to the environment.
- Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Clear.
- Colour : Clear.
- odour : Slight sweet odour.
- Odour threshold : No data available
- pH : 7
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : < 0 °C (<32 °F)
- Boiling point : > 100 °C (>212 °F)

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1 – 1.03 g/cm <sup>3</sup> (8.4 - 8.6 lb/gal)
Solubility	: Water: Soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, SiO<sub>2</sub>. Ammonia and/or derivatives. Toxic fumes may be released.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LD50 dermal rabbit	220 mg/kg
LC50 inhalation rat (ppm)	450 ppm/4h
ATE (oral)	470,000 mg/kg bodyweight
ATE (dermal)	220,000 mg/kg bodyweight

Dimethylol-5,5-dimethylhydantoin (6440-58-0)	
ATE (oral)	500,000 mg/kg bodyweight

Skin corrosion/irritation : Not classified  
pH: 7

Serious eye damage/irritation : Not classified  
pH: 7

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Carcinogenicity : Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Overexposure may cause : Headaches. The inhalation of airborne droplets or aerosols causes irritation of the respiratory tract.

Symptoms/injuries after eye contact : In fine dispersion/spraying/misting: May cause eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

2-Butoxyethanol (111-76-2)	
LC50 fishes 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

### 12.2. Persistence and degradability

Defy Interior Clear Wood Finish	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

Defy Interior Clear Wood Finish	
Bioaccumulative potential	Not established.

2-Butoxyethanol (111-76-2)	
Log Pow	0,81 (at 25 °C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources. Do not re-use empty containers. It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT

No dangerous good in sense of transport regulations

### Additional information

Other information : No supplementary information available.

### ADR

Transport document description : No additional information available

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### 2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

#### 2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Class B Division 3 - Combustible Liquid  
Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects  
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

#### Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification

Uncontrolled product according to WHMIS classification criteria

### EU-Regulations

#### 2-Butoxyethanol (111-76-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

#### Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances.

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

### 15.2.2. National regulations

#### 2-Butoxyethanol (111-76-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)  
Listed on the Canadian Ingredient Disclosure List

#### Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the AICS (the Australian Inventory of Chemical Substances)  
Listed on Inventory of Existing Chemical Substances (IECSC)  
Listed on the Korean ECL (Existing Chemical List) inventory.  
Listed on New Zealand - Inventory of Chemicals (NZIoC)  
Listed on Inventory of Chemicals and Chemical Substances (PICCS)

### 15.3. US State regulations

No additional information

# Defy Interior Clear Wood Finish

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*