

MANUFACTURER:

SaverSystems
Richmond, IN 47374
800-860-6327
Fax: 765-935-4999
www.chimneyrx.com

DESCRIPTION

Chimney RX Paint "N" Peel Fireplace Cleaner is a water-based cleaning poultice that removes unsightly smoke, soot, creosote and dirt stains from masonry fireplace fronts and hearths. No additional water is needed for application or removal. Simply paint the product on the surface, allow it to dry, and then peel it off.

USES

Product can be used to clean most all masonry surfaces both interior/exterior, textured or smooth brick, stone, marble, granite, slate, tile, concrete, mortar and limestone.

Always test for compatibility and desired results with your specific surface before proceeding with entire project. Apply product in a small inconspicuous "test" area, allow product to dry completely (6-12 hours) before removing. Heavily soiled areas may require multiple applications.

ADVANTAGES

- Restores masonry to its original appearance
- Waterless - simply paint on & peel off
- Environmentally friendly - no harsh chemicals
- Works on nearly all masonry surfaces

DIRECTIONS FOR USE

Weather Conditions: Apply when surface and air temperatures are between 45° F and 95° F.

Surface Preparation: Wipe surface with a dry or slightly damp rag to remove dust. Mask off work areas and cover all non-target surfaces with plastic or drop cloths. The use of removable painters tape is recommended to protect surfaces adjacent to product application, such as fireplace glass doors, fireplace mantles and any trim that abuts the masonry to which product is to be applied. Be sure to protect all surrounding carpet, fabric, metal, wood, and painted surfaces from inadvertent spills and roller splatter, as product may cause stains or damage to non-target surfaces. For best results, surfaces to which product is to be applied should be dust free, dry, and cool to touch before application.

Note: Do not apply while fireplace is in use.

APPLICATION

Do not thin product. Stir before use. Apply a thick, liberal coat, approximately 1/8" – 3/16" thickness using a paint brush and/or a thick nap roller. Be sure to maintain the recommended thickness across the entire surface area to be coated and near the edges of your project. Ensuring an even application will help the product peel off easily and uniformly when dry.

For areas that are more heavily soiled, agitation with a stiff nylon bristle scrub brush may be required to help the product work deeper into the surface. Once surface has been agitated, recoat to be sure a thick, even application of product remains on surface.

On extremely porous surfaces or in extremely dry conditions, it may be beneficial to lightly mist the surface with water, agitate with a soft bristle brush and blot dry with clean rags just prior to application to help prevent product from drying out too quickly.

Drying time: At 1/8"-3/16" thickness, product will take 6-12 hours to dry completely depending on environmental conditions.

Removal of Dry Product: Product must be completely dry before removing. Starting at an edge, pull the dry film off slowly at an angle with both hands. Be careful not to tear the coating as this may make it more difficult to remove. Once film is completely removed, fireplace can be put back in use.

Coverage: When applied at 1/8"-3/16" thickness, product will cover 40 - 80 sq. ft. per gallon depending on the texture and density of the surface.

CLEAN UP

Wipe excess material off of tools. Tools may then be cleaned with soap and water. Dispose of dried coating in accordance with local regulations for non-hazardous solid waste. Absorb small spills with inert material and dispose of according to local regulations. Rinse spill area with water.

CAUTIONS

Keep out of reach of children. Do not take internally. Close container after each use. Do not reuse containers. The use of protective gloves and chemical splash goggles are recommended when handling any chemical product. Wash thoroughly after handling.

FIRST AID

If inhaled: Move the affected person away from the contaminated area and into the fresh air. Ensure fresh air breathing. Allow the victim to rest. In all cases of doubt, or when symptoms persist, seek medical advice.

If swallowed: Rinse mouth. Do NOT induce vomiting. If the person is fully conscious, make him/her drink water. Never give an unconscious

person anything to drink. Obtain emergency medical attention.

For skin contact: Wipe off excess material and wash exposed skin with mild soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

For eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention immediately.

For additional information for this product, consult the Safety Data Sheet available at www.chimneyrx.com.

LIMITED WARRANTY

Our recommendations for use of this product are based upon tests believed to be reliable. Since field conditions vary widely, the user must determine the suitability of the product for the particular use and specific method(s) of application. Due to the fact that SaverSystems has no control over surface preparation and application methods, no guarantee as to results is offered, expressed or implied. SaverSystems warrants this product to be free from manufacturing defects.

SaverSystems' liability shall be limited in all events to supplying enough product to re-treat the specific areas to which defective product was applied. This warranty does not include the cost of labor application. SaverSystems shall not have any other liability including direct, incidental, or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so this limitation may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

PACKAGING

Available in half-gallon recyclable plastic containers.

TRANSPORT AND HANDLING

Chimney RX Paint "N" Peel Fireplace Cleaner is not considered hazardous under Department of Transportation (DOT) regulations. Store in a cool, dry, well ventilated place. Do not stack pallets. **Keep from freezing.**

PHYSICAL PROPERTIES

COLOR Light gray, thick paste
COMPOSITION. Proprietary blend of water miscible polymers and surfactants
WEIGHT (8.5 lbs/gallon)
VOC CONTENT (ASTM D 6886) 41 g/L
SHELF LIFE 24 months when unopened
FLASH POINT None
FREEZE/THAW STABILITY No